

Soil Compactors

MV 145 MV 205



- ◆ Easy to operate
- ◆ Hydrostatic regulation
- ◆ Dead man's grip

- ◆ Anti-vibration handle
- ◆ Protection frame
- ◆ Transport wheels and polyurethane plate as option

The forward and backward moving soil compactors TREMIX MV 145 and MV 205 are intended for compaction work at house foundations, in trenches, road and street jobs etc. Thanks to their compact design the compactors are ideal for jobs in confined spaces.

The forward / backward movement is easily controlled hydraulically. In order to prevent injuries due to squeezing or running over when the machines are moving backwards, the backward control is designed in the form of a "dead man's grip". When the machines are run backwards, the grip must be pressed against the steering handle. When pressed down, the ergonomically correct grip entirely mingles to the

shape of the handle, which makes the steering of the machine and manipulation of controls easy during backward running. In view of highest possible comfort and in order to prevent injuries due to vibrations, great attention has been given to the vibration-isolation.

The engine is protected by a steady frame. Recoil starter, carburettor, air cleaner, fuel tank. etc. are well protected against damage during operation and transportation. The protective frame is provided with a lifting eye for hoisting by crane. Transport wheels can be fitted as option. An optional polyurethane rubber plate can be easily attached to the bottom plate for concrete block tiling applications.



Concrete block tiling applications



With optional polyurethane plate

Technical data: Tremix Forward and Reversing Soil Compactors MV 145 and MV 205

Soil Compactor	MV 145	MV 205
Engine type	Honda GX 200	Yanmar L 40 AE
Net weight	183 kg	199 kg
Working weight	185 kg	201 kg
Working speed	about 24 m/min	about 24 m/min
Centrifugal force	29 000 N	29 000 N
Vibration frequency	65 Hz	65 Hz
Engine output	3,9 kW	3,1 kW
Engine speed	3500 r.p.m.	3500 r.p.m.
Fuel	Petrol	Diesel
Fuel tank volume	3,6 l	2,5 l
Plate size, WxL	450x650 mm	450x650 mm

*The pictures are illustrative only and do not necessarily show the configuration of products on the market at a given date.
The products must be used in conformity with safety practice and applicable statutes, regulations, codes and norms.
Specifications of products and equipment shown herein may be altered without notice.*



TREMIX AB, Stensåtravägen 9, Box 226,
SE-127 24 Skärholmen-Stockholm, Sweden.
Tel.int. +46 8 603 32 00. Telefax +46 8 6467261.